

4/3: WestCHEM Grouting Systems

SOLVA STRONG[®]
RANGE OF
CONSTRUCTION CHEMICALS



LOW VISCOSITY EPOXY GROUT MI

Product:



20
Kg

10
Kg

4/3: WestCHEM Grouting Systems



LOW VISCOSITY EPOXY GROUT MI

About Product

Low Viscosity Epoxy Grout MI is a two component, solvent-free, low viscosity injection liquid that is based on epoxy resin with great strength.

Uses:

An injection resin that adheres well to dry stone, steel, concrete, mortar, and other porous materials. is used to fill and seal holes and gaps in structures such as civil engineering buildings, bridges, industrial and residential buildings, e.g. floors, columns, foundations, beams, walls, and water retention structures.

Advantages:

- 1: Moisture Insensitive.
- 2: Low Viscosity.
- 3: Solvent free.
- 4: High adhesive strengths.
- 5: Suitable for arid environments.
- 6: Hardening without shrinkage.
- 7: Suitable for use at low temperatures.
- 8: High compressive strength.
- 9: High Tensile & Flexural strength.

Chemical Base	Epoxy Resin
Packaging	Part A – 20Kg (Resin) Part B – 10Kg (Hardener)
Colour	Part A: colourless Part B: colourless Part A+B mixed: colourless
Shelf Life	12 months from date of production
Storage Conditions	Store properly in unopened, undamaged and sealed original packaging, in dry conditions at temperatures between +5°C and +40°C.

Mix Density (g/cc) (ASTM D1475-2013)	1.09	
Compressive Strength (N/mm) (ASTM D695-2015)	1 Day >70	
Compressive Strength (N/mm) (ASTM D695-2015)	7 Day >80	
Consumption	1.14 kg of Low Viscosity Epoxy Grout is ~ equal to 1 l injection resin.	
Substrate Temperature	+10°C min. / +40°C max.	
Substrate Moisture Content	Dry Condition	
	Temperature	Time
	+30°C	~ 30 min

Substrate Preparation:

Sound, clean, free from oil and grease and surface treatments etc.

Pre-treatment for a strong bond:

Concrete, mortar, and stone should be completely prepared using high-pressure water jetting or mechanical methods such as grinding, chiselling, and so on. Dust must be removed from cracks using compressed air.

Concrete and mortar must be at least 28 days old (depending on the minimum strength requirements). Make sure the substrate is strong (concrete, masonry, natural stone). Similar to Sa 2.5, steel substrates must be de-rusted. It is necessary to clean up any loose debris and have a solid concrete substrate.

Mixing:

Part A: Part B = 20: 10 (by weight)

Bulk Packaging:

Add both materials in the exact proportions to a suitable clean, dry container and mix as for the pre-batch units.



LOW VISCOSITY EPOXY GROUT MI

Application Method

The treated surface must be structurally sound and free of standing water, oil, grease, and surface contaminants. The surface should be free from dirt, dust, oil grease, and other foreign material.

Crack impregnation on horizontal slabs:

Impregnation is applied with a paint brush or roller until the substrate is completely saturated. Pouring mixed **Low Viscosity Epoxy Grout MI** (Solva Strong) in the cracks seals cracks. Cracks to be sealed with thixotropic epoxy putty from the negative side of the horizontal surface. Cracked injection on horizontal/vertical slabs injection Packer/nipples are fitted along the crack line at a 150-250 c/c distance. Thixotropic epoxy putty should be used to close the crack mouth.

Injection pumps or Hand Pumps can be used to inject mixed Solva strong Low Viscosity Epoxy Grout MI under pressure through injection ports. When injection resin flows from the next injection port, the first one is shut and the injection process is restarted from the next port. For horizontal cracks, the injection should begin at any of the ends and continue until the final port is utilised. Injection should begin at the lowest port and go higher for vertical cracks. The injection ports, as well as the sealing materials between the ports, are removed once the injection procedure is completed.

Legal Notes: The information, and, in particular, the recommendations relating to the application and end-use of West Chem's products, are given in good faith based on West Chem's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with West Chem's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. West Chem reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.